

## Integrated Mapping and Modelling Solution for Manned Aircraft

WaldoAir, USA, and Pix4D, Switzerland, have announced the launch of an integrated camera system for use on single-engine aircrafts bundled with aerial image-processing software. This complete system offers the manned aircraft industry the same technological advantages of fast and cost-effective mapping and modelling that the UAV industry has been introducing over the last two years. ◀  
▶ <http://bit.ly/QbPIC4>

## GEO Business 2014 Launches Inaugural Conference Programme

Diversified Communications UK, the organiser of GEO Business, has recently announced that the final, vital component for its inaugural event is now in place following the launch of a wide-ranging conference programme. The conference committee has compiled a pioneering programme which covers the breadth of the geospatial industry. The event is scheduled to be held in London, UK, at the Business Design Centre from 28-29 May 2014. The exhibition is combined with an extensive commercial workshop programme. ◀  
▶ <http://bit.ly/QbSWA2>



GEO Business website.

## Going Oblique

The camera is the most essential part of any photogrammetric workflow as its features define the type and quality of the imagery – the ultimate resource. Since 2000, the film in the focal plane has been gradually replaced by chips, not only in cameras on the consumer market but also in highly specialised aerial cameras. The number of pixels of today's aerial cameras are counted in tens or even hundreds of megapixels (MP). The benefits of digital aerial cameras over film-based ones are well-documented; these include better radiometric resolution – commonly 16 bits per colour – and elimination of film-processing and scanning costs. Availability of digital image content supports a highly automated workflow enabling the creation of digital elevation models/digital surface models (DEM/DSM), orthomosaics and virtual 3D city and landscape models with little delay between capture and delivery. This not only allows for rapid response in the aftermath of a disaster but



MATHIAS LEMMENS  
Senior editor, GIM International  
mathias.lemmens@geomatics.nl

is also increasingly demanded by urban planners and managers who want up-to-date 2D, and increasingly 3D, data of buildings, facilities and other objects. Important camera features include the geometric and radiometric quality of lenses, focal length, the number and size of pixels, the radiometric resolution of pixels counted in number of bits, and spectral bands recorded, including panchromatic (PAN), red, green and blue (RGB), near-infrared (NIR), or green, red and near-infrared known as colour-infrared (CIR). In addition, the viewing angle, i.e. the orientation of the optical axis

in space, is key. When the optical axis intentionally points in the vertical, aerial surveys result in nadir images which are circa parallel to the terrain. The orientation of the optical axis of oblique images purposefully deviates from nadir. The size of the tilt angle determines whether the horizon is visible or not. The *Manual of Photogrammetry* (4<sup>th</sup> edition, p. 279) lists three advantages of vertical over oblique:

- Less complicated relationships in geometry
- Detection and recognition of objects is aided by the nearly normal shapes of images
- Less hidden ground (occlusion) because of less obliquity

As a result, extracting accurate geometry from aerial images on a production scale has long been limited to vertical images. Today's sensors can be calibrated accurately, georeferencing can be done through GNSS/IMU alone while today's computers can swiftly conduct the complex calculations needed for extraction of real-world coordinates from imagery. Hence, extraction of accurate geometry from oblique images, acquired by off-the-shelf products, has now become a reality. As a contribution to the series on oblique airborne imagery, I present in this issue of *GIM International* the first part of a survey on features and systems (see page 20). A follow-up article will be published in the May issue.

